

FAA
Approved
for air travel!



Made
in the
U.S.A.


iGo Portable Oxygen System
(Model 306DS-A)

CE 0044

iGo® Portable Oxygen System

Reliable Portable Oxygen On The Go

The iGo Portable Oxygen System is a **lightweight, three-liter oxygen concentrator** that is capable of operating from three different power sources: AC Power, DC Power, or Rechargeable Battery.

The DeVilbiss iGo has been put through **aggressive durability testing to ensure consistent, reliable performance**. The iGo is the perfect solution to keep pace with an active lifestyle. This small, portable oxygen system provides **two modes of operation – continuous flow or PulseDose® delivery**.

The reliability and safety of **PulseDose oxygen delivery has been proven effective in clinical testing as well as through independent tests** performed by physicians and respiratory therapists.

Performance Features

- Settings 1 to 6 in PulseDose Mode or 1 to 3 lpm in Continuous Flow Mode
- Integrated PulseDose oxygen conserving technology extends the use time, offering improved comfort and increased efficiency.
- Built in OSD® (oxygen sensing device) ensures accurate oxygen delivery and reduced periodic maintenance schedule
- 3-year limited warranty for the iGo Portable Oxygen System
- 1-year limited warranty on battery
- Increased Battery Capabilities – Can last as long as 5.4 hours when operating on setting 1 in PulseDose Mode
- Audible alerts for Power Failure, Low Battery, Low Oxygen Output, High Flow/Low Flow, No Breath Detected in PulseDose Mode, High Temperature, Unit Malfunction
- Can be used with 50 foot tubing/cannula in continuous flow mode and 35 foot tubing/cannula in PulseDose mode

Parts and Accessories

DEVILBISS PART # PRODUCT DESCRIPTION

306DS-627	Remote Humidifier Stand
444-507	Elbow Humidifier Adapter Kit
306D-413	DeVilbiss Rechargeable Battery
306DS-625	Rolling Carry Case
306DS-635	Deluxe Rolling Carry Case
306DS-626	Detachable Wheeled Cart
306DS-655	Accessory Bag
306DS-611	Air Filter

DEVILBISS PART # PRODUCT DESCRIPTION

306DS-652	DC Adapter
306DS-651	AC Adapter (Includes USA Power Cord)
306DS-601	USA Power Cord
306DS-602	Continental Europe Power Cord
306DS-603	UK Power Cord
306DS-604	Australia Power Cord
306DS-605	China Power Cord

Design Features

- High-performance capabilities, compact design weighing less than 20 lbs with battery
- Control Panel designed to be easily viewed whether unit is sitting on the ground or under an airplane seat
- Fast battery charge time – 2 to 4.5 hours dependent upon the flow setting
- Easy to read Battery Status Gauge indicates battery life
- Easy to access filter compartment
- Rolling carry case options feature easy access openings for cannula and external power supply



Rolling Carry Case
(306DS-625)



Deluxe Rolling Carry Case
(306DS-635)



Accessory Bag
(306DS-655)



Detachable Wheeled Cart
(306DS-626)

Technical Specifications

Designed to meet HCPCS Code E1392 and E1390

Weight

19 pounds (8.6 kg) with Battery; 15.5 pounds (7.0 kg) without Battery

Dimensions (H x W x D)

15" x 11" x 8" (38cm x 28cm x 20cm)

Flow Rate Settings

Settings 1 to 6 in PulseDose Mode; 1 to 3 lpm in Continuous Flow Mode

Max. Recommended Continuous Flow

3 lpm

Oxygen Concentration

91% ± 3% for all flow settings

Operating Temperature

41°F to 104°F (5°C to 40°C)

Transportation and Storage Temperature

-4°F to +140°F (-20° to 60°C)

Altitude

0 – 13,123 feet (0 – 4,000 meters) tested @ -933 hPa

Sound Level (3.0 PulseDose Mode)

40 dBA



DeVilbiss Healthcare LLC | 100 DeVilbiss Drive | Somerset, PA 15501 USA
800.338.1988 | 814.443.4881 | www.DeVilbissHealthcare.com